


[illegible]




Fig.2a




Fig. 2b




Fig. 2c




Fig. 2d

PhoneFree registration page can be found at:
<http://phonefree.com/install/addquickform2.html>

Partial screen shot:

PhoneFree.com Survey - Microsoft Internet Explorer

File Edit View Favorites Tools Help

Address <http://phonefree.com/install/addquickform2.html>

Back Forward Stop Refresh

PhoneFree Registration PHONEFREE.COM

In order to keep PhoneFree free, we need to ask you for some demographic information. All information will be kept strictly private.

To be perfectly honest, the reason we ask you to fill out the form is so that we can serve you advertising that will hopefully be of interest to you. It only takes a few minutes and we appreciate your joining PhoneFree.

White Pages Listing Information

First Name

Last Name

City

Country

State (U.S. only)

Zip Code (US Only)

If you would like to include comments with your listing, please enter them here:

Your White Pages listing style

☐ General Listing

☐ Unlisted

☐ Friends & Family Only

(This option simply places the words "Friends and Family Only" next to your listing)

Password

Please choose a password with which to access your account

Internet

Fig. 3a




Fig. 36




Fig. 4a

Copyright 1996 by International Business Machines Corporation. All rights reserved. IBM, the IBM logo, and the e-business logo are trademarks of International Business Machines Corporation. Other names may be trademarks of their respective owners.





FIG. 5


FIG. 6 is a flowchart illustrating a method for establishing a connection between a caller and a callee through a proxy. The flowchart is divided into three main sections: CALLER, PROXY, and CALLEE. The CALLER section starts with a 'start' node, followed by a 'get address' block (receiving input from a 'proxy IP' block). This is followed by a 'connect' block, then a 'talk' block. A decision diamond 'hangup?' follows; if 'yes', it goes to an 'end' node; if 'no', it loops back to the 'talk' block. The PROXY section starts with a 'start' node, followed by an 'accept' block (receiving a 'connect message' from the CALLER's 'connect' block). This is followed by a 'get address' block (receiving input from a 'callee IP' block), then an 'echo from caller' block, then an 'echo' block. A decision diamond 'hangup?' follows; if 'yes', it goes to an 'end' node; if 'no', it loops back to the 'echo' block. The CALLEE section starts with a 'start' node, followed by an 'accept' block (receiving a 'connect message' from the PROXY's 'echo from caller' block). This is followed by a 'talk' block. A decision diamond 'hangup?' follows; if 'yes', it goes to an 'end' node; if 'no', it loops back to the 'talk' block. Communication between the sections is as follows: The CALLER's 'talk' block sends 'UDP from caller' to the PROXY's 'echo' block and 'TCP to caller' back to itself. The PROXY's 'echo' block sends 'TCP from callee' to the CALLEE's 'talk' block and 'TCP (case 2) or UDP (case 3) to callee' back to itself. The CALLEE's 'talk' block sends 'TCP from callee' to the PROXY's 'echo' block and 'TCP (case 2) or UDP (case 3) to callee' back to itself. The flowchart is titled 'FIG. 6' at the bottom.

CALLER

A client that cannot receive UDP



PROXY



Case 2:
Caller is behind a firewall, and can send UDP, but only receive TCP. Callee can receive UDP, but only send TCP.

Case 3:
Caller is behind a firewall, and can send UDP, but only receive TCP. Callee can only send and receive TCP.

CALLEE

A client that cannot send UDP






FIG. 6

CALLER

A client that cannot send
UDP



PROXY



Case 5:
Caller can receive
UDP, but only
send TCP. Callee
can send UDP, but
only receive TCP.

Case 9:
Caller can only
receive and send
TCP. Callee can
send UDP, but
only receive TCP.

CALLEE

A client that cannot
receive UDP




FIG. 7

the only way to get the data from the caller is to get the data from the caller in the first place.




FIG. 8




FIG. 9

Copyright 1994 by International Business Machines Corporation. All rights reserved. IBM, the IBM logo, and the "Think" logo are trademarks of International Business Machines Corporation. Other names may be trademarks of their respective owners.




FIG. 10




FIG. 11

Figure 12: A sequence diagram showing the interaction between a Caller, a Proxy, and a Callee. The Caller is a client speaking UDP. The Proxy is a client that can receive UDP, but send either TCP or UDP. The Callee is a client that can receive UDP, but send either TCP or UDP. The diagram illustrates the flow of messages and the state of each entity during the process.




FIG. 12